PATENT ABSTRACTS OF JAPAN

(11)Publication number:

10-208545

(43) Date of publication of application: 07.08.1998

(51)Int.CI.

H01B 1/12 C08F293/00

(21)Application number: 09-024267

(71)Applicant: SHIN ETSU CHEM CO LTD

(22)Date of filing:

23.01.1997

(72)Inventor: HIRAHARA KAZUHIRO

NAKANISHI NOBORU ISONO YOSHINOBU TAKANO ATSUSHI

(54) MANUFACTURE OF CROSS-LINKING TYPE POLYMERIC SOLID ELECTROLYTE AND CROSS-LINKING POLYMERIC SOLID ELECTROLYTE

(57)Abstract:

PROBLEM TO BE SOLVED: To restrain swelling and dissolving with respect to a various kinds of electrolytes and obtain superior electrolyte liquid maintenance, mechanical strength, and molding property and high ion conductivity by adding a cross-linking agent to a block-graft co-polymer of specific co-polymerization degree having two kinds of block chains of a specific rate, irradiate high energy rays, and adding non-aqueous electrolyte after crosslinking. SOLUTION: A component rate between a block chain A of, co-polymer of 10 or more in polymerization degree comprising a repetition unit of formula I and a block chain B of 300 or more in polymerization degree comprising a repetition unit of formula III is 1:30 to 30:1. This co-polymer in which polymerization degree is 310 or more is crosslinked with addition of a cross-linking agent and high-energy irradiation, after which a non-aqueous electrolyte is added. [In formulas I and III, R1 and R4 are hydrogen, methyl group, and ethyl group; R2 is hydrogen or methyl group; R3 is alkyl group, aryl group, acyl group, silyl group, cyano-alkyl group;

n is an integer of 1 to 100; and a number-average molecule weight of graphite chain expressed by formula II is 45 to 440; M is a group expressed by formula IV, phenyl group or the like].

LEGAL STATUS

[Date of request for examination]

19.07.2000

[Date of sending the examiner's decision of

08.04.2003

rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or